

Weldac® 600



Less power consumption, a smaller footprint and easier operation are three hallmarks of the latest generation of Weldac systems. These features, coupled with the reliability of IGBT transistors, translate into:

More uptime

EFD Induction's patented switching pattern lets Weldac use rugged IGBT transistors. These transistors are virtually short-circuit proof, considerably boosting Weldac's reliability.

More output

Continuous electronic load matching secures full power output across a wide range of tube sizes, ensuring maximum welding speed for each size. No operator action is needed, simply change the coil size.

Lower costs

Weldac's efficiency from input at the rectifier to output at the coil is 85-87%. Cooling water consumption is low, with no need for expensive de-ionized water. Weldac eliminates the need for costly reactive power compensation capacitors by using diode rectifiers that result in a high, constant power factor (0.95) at all power levels.



Weldac® 600

PRODUCT FEATURES

One-cabinet design

The entire Weldac converter is housed in one cabinet. This minimizes the total converter footprint. The need for an HF cable to a heating station or a DC cable from a rectifier unit is eliminated. The use of one cabinet also simplifies transportation and minimizes installation cost and time.

Power savings

Weldac features a diode rectifier with a constant power factor of 0.95 at all power levels. There is no reactive power cost, and no need for compensating capacitors.

Rugged IGBT transistors

Our patented driver technology lets Weldac use standard reliable IGBT transistors for better uptime and output.

Full output power

Weldac's automatic load matching ensures full output power across a wide range of tube sizes. There are no 'unsafe' operating areas. When a different-sized coil is fitted, Weldac automatically matches to the best setting.

Clean weld bead

Weldac's low ripple results in a clean weld bead—making it ideal for stainless steel and aluminum welding.

Short circuit resistant

IGBT transistors, together with an advanced switching pattern and intermediate transformer design, make Weldac short-circuit resistant.

On-site upgrades

Weldac's modular design makes it possible to upgrade power in order to handle future production increases.

Advanced MMI

Weldac features the latest in Man/Machine Interface (MMI) control panels. Moreover, Weldac can operate with most currently available major bus interfaces.



OPTIONS / ADDITIONALS

One- or three-axis positioning tables, water/water, plate-type heat exchanger, quality monitoring system (QMS), field bus communication, temperature monitoring/control systems, input auto transformer, tacho generator, impeders and coils.

TECHNICAL DATA

Model	Weldac 600
Output	
Continuous output power	600 kW
Output power regulation range	10-100 %
Frequency range	160-240 kHz
Efficiency	> 0.85
Supply	
Supply voltage range	3x 480 V ± 10%
Frequency	50/60 Hz
Nominal line current	970 A (RMS)
Nominal apparent power	806 kVA
Power factor (cos φ)	> 0.95

Cooling

Water consumption, min.	140 l/min
Water inlet temperature	max. 35°C
Water pressure min./max.	4.5/6 bar
Cooling water quality - ph	between 7.0 and 9.0

Enclosure

Ambient operating temp.	+5°C - +50°C
Dimensions excl. busbar (LxWxH)	2430x600x2000 mm
Busbar length to coil connection	840 mm
Weight	900 kg
Enclosure protection	IP 54
Color	RAL 7035 Grey

Subject to modification